

**产品规格书****Specification of Product**

产品名称: 7.4V 60公斤串行总线舵机 Name: 7.4V 60kg-cm Serial Control BUS Servo	Product
产品型号 Model No. SCS6560M	

1. 使用环境条件 Apply Environmental Condition

No.	Item	Specification
1-1	存储温度 Storage Temperature Range	-30°C~80°C
1-2	运行温度 Operating Temperature Range	-15°C~70°C

2. 测试环境 Standard Test Environment

No.	Item	Specification
2-1	温度 Temperature range	25°C ±5°C
2-2	湿度 Humidity range	65%±10%

3. 机械特性 Mechanical Specification

No.	Item	Specification
3-1	尺寸 Size	A: 65.8mm B: 30mm C: 59.75mm
3-2	重量 Weight	200g
3-3	齿轮类型 Gear type	Metal Gear
3-6	机构极限角度 Limit angle	No
3-7	轴承 Bearing	2 Ball bearings
3-8	出力轴 Horn gear spline	15T
3-9	摆臂 Horn type	Plastic, POM
3-10	外壳 Case	Engineering plastics & Aluminium
3-11	舵机线 Connector wire	150mm ±5 mm
3-12	马达 Motor	Core motor
3-13	防水性能 Splash water resistance	No

4. 电气特性 Electrical Specification (Function of the Performance)

No.	工作电压 Operating Voltage Range	6V	7.4V
4-1*	静态电流 Idle current(at stopped)	5mA	6.0mA
4-2*	空载速度 No load speed	0.15sec/60°	0.13 sec/60°
4-3*	空载电流 Runnig current(at no load)	190 mA	250 mA
4-4	堵转扭矩 Peak stall torque	48kg. cm	62kg. cm
		666.56 oz. in	861 oz. in
4-5	堵转电流 Stall current	2400 mA	2900 mA

Note: "*"definition is average value when the servo runing with no load

产品名称: 7.4V 60公斤串行总线舵机
Product
Name: 7.4V 60kg-cm Serial Control BUS Servo
产品型号 Model No. SCS6560M
5. 控制特性 Control Specification:

No.	Item	Specification
5-1	控制信号 Command signal	Bus Packet Communication TTL level
5-2	放大器类型 Amplifier type	Half duplex Asynchronous Serial Communication
5-3	脉冲宽度范围 Pulse width range	0-253
5-4	中立位置 Neutral position	38400bps ~ 1 Mbps
5-5	旋转角度 Running degree	300° (when 0~1023)
5-6	死区宽度 Dead band width	Load, Speed, Input Voltage
5-7	旋转方向 Rotating direction	Potentiometer (300° /1024)

6. 外形图 The Drawings
